

### Hex Wrench Dimensions and Specifications

Hex Wrench Model and Housing	Max. AF Size		Max. Torque Output		R		L		W		H	
	mm	in	N-m	lb-ft	mm	in	mm	in	mm	in	mm	in
RSL2H014	22	7/8	433.9	320	20.1	0.79	152.4	6	31.8	1.25	110	4.33
101	27	1 1/16	867.7	640	24.1	0.95	153.7	6.05	31.8	1.25	114.3	4.5
104	31	1 1/4	867.7	640	26.2	1.03	155.4	6.12	31.8	1.25	116.1	4.57
107	36	1 7/16	1220.2	900	29.2	1.15	158.5	6.24	31.8	1.25	119.1	4.69
110	42	1 5/8	1909	1408	33.4	1.31	162.8	6.41	31.8	1.25	123.4	4.86
113	46	1 13/16	1909	1408	35.5	1.4	164.8	6.49	31.8	1.25	125.5	4.94
200	50	2	1909	1408	37.7	1.48	167.1	6.58	31.8	1.25	127.8	5.03
203	55	2 3/16	1909	1408	40.1	1.58	169.7	6.68	31.8	1.25	130.3	5.13
206	60	2 3/8	1909	1408	43.2	1.7	172.5	6.79	31.8	1.25	133.1	5.24
RSL4H104	32	1 1/4	813.5	600	26.2	1.03	189.2	7.45	35.1	1.38	135.9	5.35
107	36	1 7/16	1220.2	900	30	1.18	193.5	7.62	35.1	1.38	139.4	5.49
110	41	1 5/8	1627	1200	33.5	1.32	197.4	7.77	35.1	1.38	143	5.63
113	46	1 13/16	2576	1900	37.3	1.47	199.9	7.87	35.1	1.38	146.8	5.78
200	50	2	3525.1	2600	40.6	1.6	204.2	8.04	35.1	1.38	150.4	5.92
203	55	2 3/16	4175.9	3080	44.7	1.76	207.3	8.16	35.1	1.38	154.4	6.08
206	60	2 3/8	4175.9	3080	46.7	1.84	209.6	8.25	35.1	1.38	156.2	6.15
209	65	2 9/16	4175.9	3080	49.5	1.95	206.8	8.14	35.1	1.38	159	6.26
212	70	2 3/4	4175.9	3080	51.8	2.04	209	8.23	35.1	1.38	161.5	6.36
215	74	2 15/16	4175.9	3080	54.9	2.16	211.8	8.34	35.1	1.38	166.1	6.54
RSL6H200	50	2	3525.1	2600	40.9	1.61	230.6	9.08	44.5	1.75	165.6	6.52
203	55	2 3/16	4745.3	3500	43.4	1.71	233.2	9.18	44.5	1.75	168.1	6.62
206	60	2 3/8	6101.1	4500	47.5	1.87	237.2	9.34	44.5	1.75	172.2	6.78
209	65	2 9/16	7189.8	5303	51.1	2.01	240.8	9.48	44.5	1.75	175.8	6.92
212	70	2 3/4	7189.8	5303	54.9	2.16	244.6	9.63	44.5	1.75	179.6	7.07
215	75	2 15/16	7189.8	5303	56.9	2.24	246.6	9.71	44.5	1.75	181.6	7.15
302	80	3 1/8	7189.8	5303	57.4	2.26	247.1	9.73	44.5	1.75	182.1	7.17
RSL8H203	55	2 3/16	4745.3	3500	43.4	1.71	238	9.37	57.2	2.25	173.7	6.84
206	60	2 3/8	6101.1	4500	47.5	1.87	242.1	9.53	57.2	2.25	177.8	7
209	65	2 9/16	7863.6	5800	53.3	2.1	245.6	9.67	57.2	2.25	181.1	7.13
212	70	2 3/4	10659.3	7862	54.9	2.16	249.4	9.82	57.2	2.25	184.9	7.28
215	75	2 15/16	10659.3	7862	56.9	2.24	251.5	9.9	57.2	2.25	186.9	7.36
302	-	3 1/8	10659.3	7862	57.4	2.26	252	9.92	57.2	2.25	187.7	7.39
302	80	-	9897.3	7300	57.4	2.26	252	9.92	57.2	2.25	187.7	7.39
RSL14H209	65	2 9/16	7863.6	5800	50.3	1.98	254	10	63.5	2.5	204	8.03
212	70	2 3/4	9897.3	7300	55.6	2.19	284.5	11.2	63.5	2.5	209	8.23
215	75	2 15/16	12202.2	9000	58.2	2.29	287.3	11.31	63.5	2.5	211.8	8.34
302	79	3 1/8	15122.6	11154	61.7	2.43	290.6	11.44	63.5	2.5	215.1	8.47
308	89	3 1/2	15122.6	11154	66	2.6	297.4	11.71	63.5	2.5	219.5	8.64
314	98	3 7/8	15122.6	11154	73.2	2.88	302	11.89	63.5	2.5	226.6	8.92
404	108	4 1/4	15122.6	11154	75.7	2.98	304.8	12	63.5	2.5	229.4	9.03
410	117	4 5/8	15122.6	11154	82.6	3.25	311.7	12.27	63.5	2.5	236.2	9.3
RSL20H302	79	3 1/8	14913.8	11000	62.2	2.45	323.1	12.72	69.9	2.75	239.8	9.44
308	89	3 1/2	21692.8	16000	70.4	2.77	331.2	13.04	69.9	2.75	247.9	9.76
314	98	3 7/8	25547.3	18843	74.9	2.95	335.8	13.22	69.9	2.75	252.5	9.94
404	108	4 1/4	25547.3	18843	83.8	3.3	344.7	13.57	69.9	2.75	261.1	10.28
410	117	4 5/8	25547.3	18843	87.4	3.44	348.2	13.71	69.9	2.75	264.9	10.43
RSL30H308	89	3 1/2	21692.8	16000	65	2.56	364.7	14.36	76.2	3	267.7	10.54
314	98	3 7/8	29827.6	22000	74.2	2.92	364.7	14.36	76.2	3	273.6	10.77
404	108	4 1/4	37965.1	28002	83.6	3.29	367.5	14.47	76.2	3	283	11.14
410	117	4 5/8	37965.1	28002	87.1	3.43	371.1	14.61	76.2	3	286.5	11.28
500	127	5	37965.1	28002	92.7	3.65	376.7	14.83	76.2	3	292.1	11.5
506	136	5 3/8	37965.1	28002	96.3	3.79	380.2	14.97	76.2	3	295.7	11.64
512	146	5 3/4	37965.1	28002	102.9	4.05	386.8	15.23	76.2	3	302.3	11.9
602	155	6 1/8	37965.1	28002	107.2	4.22	393.2	15.48	76.2	3	308.6	12.15