

### Square Drive Dimensions and Specifications

Model	Wrench Head	Max. Torque Output		Sq. Drive Size	W (width)		W1 (width1)		H (height)		L (length)		L1 (length1)		R (radius)		Weight					
					in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	PowerHead		Reaction Arm		Square Drive Head	
		lb-ft	N-m	in	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg	lb	kg	lb	kg
RSL2	Sq. Drive	1408	1909	4-Mar	1.3	32	2.3	58	4.5	114	6.3	160	7.5	189	0.94	24	3.98	1.81	0.5	0.23	2.53	1.15
RSL4	Sq. Drive	3080	4176	1	1.5	38	2.88	73	5.6	141	7.7	195	10	262	1.25	32	5.69	2.58	2.28	1.03	4.75	2.15
RSL6	Sq. Drive	5303	7190	1 1/2	1.8	45	3.71	94	6.4	163	9.3	235	12	296	1.52	39	9	4.08	3.96	1.8	9.08	4.12
RSL8	Sq. Drive	7862	10659	1 1/2	2.4	61	4.14	105	6.7	169	9.5	241	12	300	1.52	39	10.8	4.9	4.32	1.96	11.25	5.1
RSL14	Sq. Drive	11154	15123	1 1/2	2.5	64	4.63	118	7.9	201	11	284	12	315	1.88	48	11.63	5.28	6.54	2.96	16.62	7.54
RSL20	Sq. Drive	18843	25548	2 1/2	3.3	83	6.38	162	9.5	241	13	342	19	482	2.5	64	20.1	9.12	15.9	7.21	29.04	13.17
RSL30	Sq. Drive	28002	37965	2 1/2	3.5	89	6.54	169	10	263	14	358	21	536	2.5	64	21.34	9.68	11	4.99	36.75	16.67